

Front

Align With Edge Of Disc

Align With Edge Of Disc

Move template this way to line up holes

Move template this way to line up holes

Move template this way to line up holes

Align With Edge Of Disc

Brake disc
- less than 7mm (1/4") thick
Locking area for the pin

XENA disc-lock alarms are designed to fit 99% of standard motorcycle brake-discs. There are three relevant measurements (for full specs and instructions, please see the Products section at www.xenasecurity.com):

- Thickness of brake-disc: Standard on all models at 7mm (1/4")
- Locking-pin size: from 6mm (1/4") to 18mm (3/4") (according to model)
- Distance from locking-pin to back of lock*: from 42mm (1 5/8") to 65mm (2 1/2") (according to model)

* Note that the locking pin can pass through ANY hole on the brake disc (see red areas on diagram).

XN14 XH14 XM14

XZN8

XN10 XD10

XZZ6

XR1 XZ1

DISC LOCK ALARM
XENA ALARMED DISC-LOCK

XN15 XE15 XH15

XN18

XENA
INTELLIGENT SECURITY

www.xenasecurity.com

Insert to check disc thickness

Copyright © MGX Asia Ltd. All rights reserved

Back

DISC LOCK ALARM
XENA ALARMED DISC-LOCK

Choose your XENA
A XENA alarmed disc-lock doesn't just warn thieves, shock & movement sensors linked to a piercing alarm help remind you to remove your lock long before you disappear over the handlebars.

All models feature:

- 110dB Alarm
- Auto-Arm / Dis-arm
- High-strength Steel Lock
- Dual Shock & Movement Sensor
- Maximum Security Key and Barrel
- Ice Spray-Proof Key and Barrel
- Microprocessor Controlled
- Detachable Electronic Module

XENA
INTELLIGENT SECURITY

SOLD SECURE

CLASSE SRA

Thatcham

VAT

ART

www.xenasecurity.com

Copyright © MGX Asia Ltd. All rights reserved

Scale

